



TUVANOR, SA
Av. Valgrande, 14 (Naves 32-33)
28100 Alcobendas (Madrid)
Tel. 91 661 82 88
Fax 91 661 82 89

Válvulas de globo Fig. 95



PN-16, cuerpo latón, cierre caucho, roscadas.
 Aplicaciones: agua.

<u>Medida</u>	<u>Euros</u>
1/2	8,28
3/4	9,15
1"	12,20
1 1/4	20,04
1 1/2	24,40
2"	34,43
2 1/2	77,56
3"	107,19

Válvulas de globo Fig. 95-B



PN-16, cuerpo y cierre bronce, roscadas.
 Aplicaciones: agua, vapor, aire e hidrocarburos

<u>Medida</u>	<u>Euros</u>
1/2	18,37
3/4	26,72
1"	38,40
1 1/4	53,44
1 1/2	65,13
2"	98,53
2 1/2	217,10
3"	280,56

Válvulas de seguridad



Graduable, escape conducido, cuerpo bronce, cierre teflón roscadas, resorte acero cromado, tornillo para regulación.
 Presión tara entre 4 y 12 kg/cm².

Aplicaciones: agua, aire e hidrocarburos.

<u>Medida</u>	<u>Euros</u>
1/2	35,07
3/4	45,10
1"	53,45
1 1/4	88,51
1 1/2	118,40
2"	163,40

Grifo macho, Fig. 76



PN-16, cuerpo y cierre latón roscadas

<u>Medida</u>	<u>Euros</u>
3/8	7,80
1/2	10,68
3/4	15,23
1"	21,71
1 1/4	40,10
1 1/2	55,11
2"	85,17

Válvulas de retención a clapeta



PN-25, cuerpo bronce, asiento goma o bronce, roscadas.
 Aplicaciones: agua e hidrocarburos.

<u>Medida</u>	<u>Euros</u>
1/2	7,41
3/4	8,28
1"	13,07
1 1/4	17,87
1 1/2	25,27
2"	37,43
2 1/2	74,07